

ITA Product Code	SIZE	PR	PATTERN	APPLICATION	L.I.	S.I.	RIM WIDTH (INCH)	SINGLE MAX LOAD (LBS) AT COLD INFLATION (PSI)	DUAL MAX LOAD (LBS) AT COLD INFLATION (PSI)	SECTION WIDTH (INCH)	OUTER DIAMETER (INCH)	STATIC LOADED RADIUS (INCH)	TREAD DEPTH (32nd Inch)	WEIGHT (LBS)	40'HC QTY	REV. PER MILE
RS102	11R22.5	14PR	R222	STEER W/ DG	144/142	M	8.25	6175 / 105	5840 / 105	11.0	41.5	19.3	18	126	276	498
RS104	11R24.5	14PR	R222	STEER W/ DG	146/143	M	8.25	6610 / 105	6005 / 105	11.0	43.5	20.3	18	135	222	475
RS112	295/75R22.5	14PR	R222	STEER W/ DG	144/141	M	9	6175 / 110	5675 / 110	11.7	40.0	18.7	18	116	268	522
RS114	285/75R24.5	14PR	R222	STEER W/ DG	144/141	M	8.25	6175 / 110	5675 / 110	11.2	41.4	19.4	19	121	248	504
RA202	11R22.5	16PR	LA160	ALL POSITION HWY	148/145	M	8.25	6940 / 120	6395 / 120	11.0	41.5	19.3	22	130	236	477
RA204	11R24.5	16PR	LA160	ALL POSITION HWY	149/146	M	8.25	7160 / 120	6610 / 120	11.0	43.5	20.3	22	141	254	500
RA222	255/70R22.5	16PR	LA160	ALL POSITION HWY	140/137	M	7.5	5510 / 120	5070 / 120	10.0	36.6	17.1	18	95	344	563
RA212	295/75R22.5	14PR	LA160	ALL POSITION HWY	144/141	M	9	6175 / 110	5675 / 110	11.7	40.0	18.7	22	125	268	522
RA214	285/75R24.5	14PR	LA160	ALL POSITION HWY	144/141	M	8.25	6175 / 110	5675 / 110	11.2	41.4	19.4	22	126	248	504
RA247	215/75R17.5	16PR	LA160	ALL POSITION HWY	135/133	J	6	4805 / 125	4540 / 125	8.3	30.2	14.2	16	65	594	687
RA259	225/70R19.5	14PR	LA160	ALL POSITION HWY	128/126	J	6.75	3970 / 110	3750 / 110	8.9	32.0	15.1	18	73	510	653
RA269	245/70R19.5	14PR	LA160	ALL POSITION HWY	133/131	M	7.5	4540 / 110	4300 / 110	9.8	33.1	15.4	18	79	464	632
RT302	11R22.5	14PR	R910	TRAILER POSITION HWY	144/142	L	8.25	6175 / 105	5840 / 105	11.0	41.5	19.3	13	115	248	503
RT304	11R24.5	14PR	R910	TRAILER POSITION HWY	146/143	L	8.25	6610 / 105	6005 / 105	11.0	43.5	20.3	13	124	238	480
RT312	295/75R22.5	14PR	R910	TRAILER POSITION HWY	144/141	L	9	6175 / 110	5675 / 110	11.7	40.0	18.7	13	114	254	524
RT314	285/75R24.5	14PR	R910	TRAILER POSITION HWY	144/141	L	8.25	6175 / 110	5675 / 110	11.2	41.4	19.4	13	115	250	508
RD402	11R22.5	14PR	R610	CLOSED SHOULDER DRIVE	144/142	L	8.25	6175 / 105	5840 / 105	11.0	41.5	19.3	28	135	248	496
RD404	11R24.5	14PR	R610	CLOSED SHOULDER DRIVE	146/143	L	8.25	6610 / 105	6005 / 105	11.0	43.5	20.3	28	146	222	473
RD412	295/75R22.5	14PR	R610	CLOSED SHOULDER DRIVE	144/141	L	9	6175 / 110	5675 / 110	11.7	40.2	18.7	28	130	254	518
RD414	285/75R24.5	14PR	R610	CLOSED SHOULDER DRIVE	144/141	L	8.25	6175 / 110	5675 / 110	11.2	41.4	19.4	28	132	250	500
RD502	11R22.5	14PR	LD102	OPEN SHOULDER DRIVE	144/142	L	8.25	6175 / 105	5840 / 105	11.0	41.5	19.3	28	135	250	500
RD504	11R24.5	14PR	LD102	OPEN SHOULDER DRIVE	146/143	L	8.25	6610 / 105	6005 / 105	11.0	43.5	20.3	28	145	230	477
RD512	295/75R22.5	14PR	LD102	OPEN SHOULDER DRIVE	144/141	L	9	6175 / 110	5675 / 110	11.7	40.2	18.7	28	132	268	517
RD514	285/75R24.5	14PR	LD102	OPEN SHOULDER DRIVE	144/141	L	8.25	6175 / 110	5675 / 110	11.2	41.4	19.4	28	132	248	500
RD659	225/70R19.5	14PR	LD122	OPEN SHOULDER DRIVE	128/126	J	6.75	3970 / 110	3750 / 110	8.9	32.0	15.1	19	75	510	652
RD669	245/70R19.5	16PR	LD122	OPEN SHOULDER DRIVE	136/134	M	7.5	4940 / 120	4675 / 120	9.8	33.1	15.4	19	78	464	632
RA702	11R22.5	16PR	R815	MIXED SERVICE RIB	148/144	M	8.25	6940 / 120	6170 / 120	11.0	41.5	19.3	20	124	254	501
RA704	11R24.5	16PR	R815	MIXED SERVICE RIB	149/146	M	8.25	7160 / 120	6610 / 120	11.0	43.5	20.3	20	135	236	478
RA732	315/80R22.5	20PR	R815	MIXED SERVICE RIB	156/153	J	9	8810 / 123	8045 / 123	12.3	42.4	19.7	21	149	213	490



R222



LA160



R910



R610



LD102



LD122



R815